

ZL520YA Quad Sealing Bag for Granular Product



It's configured to produce four corner edge sealing quad seal bags, it's also available to do pillow and gusset bag by option.

Features

- User friendly PLC controller & Touch screen interface
- Unique back-seal design are extremely flexible to run quad seal, pillow, gusset bag.
- Independent temperature zones
- Servo-driven film transport and cross sealing jaw
- Vacuum pump assists film transport
- Guarding style allows greater access & easy maintenance
- Fully enclosed stainless steel & aluminum construction
- Robust long-life construction

Technical Specifications

Model	ZL520YA	ZL720YA
Bag style	Quad Seal Bag, pillow and gusset bag	
Bag length	Up to 340mm (13.4")	Up to 420mm (16.5")
Bag width	80 to 240mm (3.1" to 7.9")	100 to 330mm (4" to 9.4")
Bag Side depth	50 to 100mm (2" to 3.9")	50 to 120mm (2" to 4.7")
Edge Seal width	5 to 10mm (0.2" to 0.4")	
Film width	≤520mm (21.3")	≤730mm (28.7")
Voltage	AC220V/50Hz, 1phase or Per customer specification	
Power Consumption	3KW	4KW
Compressed Air Requirement	0.6 MPa, 0.36 M3/min (87 Psi, 12.7cfm)	