

## UN300ZS Plus Servo Flow Wrapper



Compare with traditional UN300ZS plus servo flow wrapper, UN300ZS plus servo flow wrapper is controlled by servomotor, which brings stable convey belt speed, good package integrity and high productivity. In addition, The improved UN300 plus servo flow wrapper can realize the old and new film connection smoothly without stopping the machine, thus reduce the time of film replacement greatly improve efficiency. What's more, UN300 plus adopts PC control screen, which makes operators easier to use. Therefore, the operation training is needless.

UN300 servo flow wrapper adopts up-film packing form. Varieties of composite films are available to package deckle-edge products and products with crumbs or burrs such as biscuit. Moreover, UN300ZS plus servo flow wrapper could package single or multiple products of various types including biscuit, chocolate, and cakes as well as cards, daily necessities, etc.

### Main Specification

Max. Production Capacity	30-140bags/min (Single Cutter)	80-290(Double Cutter)	80-350(Three Cutter)
Shape of products	Square, rectangle, circular, ellipse and flake etc.		
Packaging Range	Bag Length	170-400mm	80-300mm
	Width	35-100mm	
	Height	< 60mm	< 40mm
Max Width of Film	300mm		
Max. Dia of Film	Ø350mm		
Gross Power	3Kw		
Power Supply	220V 50Hz		
Gross Weight	900kg		
Overall Dimension	4300×850×1550mm		