

## *ZG8-150 Pre-made Doy Packer Automatic Filling Packaging Machine*



Standup bag, Portable bag, Zipper bag, 4-side sealing bag, 3-side sealing bag. paper bag, type beg etc, and al kinds of compound bags.

### **Features**

1. High speed: max speed for double feeding is 90 bags/min;
2. Wide applications: various shapes, state and nature of products;
3. A wide range of pouches: all kinds of pre-made pouches;
4. Easy to operate: PLC controller, HMI system makes easy operation;
5. Easy to adjust Realize full automation, input parameters to Hmi system, each part of machine automatically adjust to required instruction;
6. High Automation: unmanned in weighing and packing process, machine alarm automatically when failure;
7. Perfect Prevention System. When the bag is not open or not opened enough, it will be non-filling and non-sealing, so the bags can be reused and not wasted and it will save the production cost,
8. The product contact parts are adopted SUS304 to ensure sanitation and safety, meet the GMP standard;
9. Imported tolerance plastic bearings: without refueling, reduce the potation of Material;
10. Vacuum Generator: low consumption, high efficiency, cleanness, and long use Life;
11. Premade bag packing: Perfect sealing quality, upgrade the finished product.

## Technical Parameters

Model	ZG8-150
Equipment material	304 stainless steel
Pneumatic component	SMC,AirTAC
Vacuum component	Vacuum generator (SMC)
Drive mode	Frequency conversion motor drive
Operation interface	Touch screen(double language:Chinese and English)
Bag materials	Heat sealable film as PA/PE,PET/PE,AL film etc.
Bag size	W:75~165mm L:100~300mm
Filling range	10~500g
Packing speed	60~90bags/min (depended on the product and filling weight)
Package accuracy	Error $\leq$ $\pm$ 1%
Weight	3000KG
Dimension	2865mm*1645mm*2000mm(L,W,H)
Total power	3kw
Power source	380V/ 3P/ 5L/ 50HZ
Compress air requirement	$\geq$ 1m <sup>3</sup> /min (compress air is provided by user)